

**AGFA AP94 - FH**

**Standard RA4 - 45 sec**

		<b>AGFA AP94</b>		<b>FH</b>			
		<b>Productname</b>	<b>temp</b>	<b>reprate</b>	<b>Productname</b>	<b>temp</b>	<b>reprate</b>
<b>Developers</b>	AP94 CD-R (Prof.)	35 ± 0.5	215 ml/m <sup>2</sup> (*)	CPRA Pro Developer	35 ± 0.3	250 ml/m <sup>2</sup>	
	AP94 CD-LR (Prof.)	35 ± 0.5	160 ml/m <sup>2</sup>	CPRA Digital Pro Developer AC	35 ± 0.3	215 ml/m <sup>2</sup> (**)	
	AP94 CD-LOR (Prof.)	38 ± 0.5	70-80 ml/m <sup>2</sup>	CPRA Developer AC	35 ± 0.5	160 ml/m <sup>2</sup>	
				EnviroPrint Developer MP160	38 ± 0.3	160 ml/m <sup>2</sup>	
				EnviroPrint Developer MP108	38 ± 0.3	108 ml/m <sup>2</sup>	
				EnviroPrint Developer MP73 AC	38 ± 0.3	73 ml/m <sup>2</sup>	
				EnviroPrint Developer MP60	38 ± 0.3	60 ml/m <sup>2</sup>	
EnviroPrint Developer MP45 AC	38 ± 0.3	45 ml/m <sup>2</sup>					
<b>Bleach-fix</b>	AP94 BX-MR (Prof.)	30-36	215 ml/m <sup>2</sup>	EnviroPrint Bleach-Fix 215 AC	33 ± 3	215 ml/m <sup>2</sup>	
	AP94 BX-LOR Prof.	30-36	100 ml/m <sup>2</sup>	CPRA Pro Bleach-Fix AC	33 ± 3	215 ml/m <sup>2</sup>	
				CPRA Digital Pro Bleach-Fix AC	33 ± 3	215 ml/m <sup>2</sup>	
				EnviroPrint Bleach-Fix 108 AC	33 ± 3	108 ml/m <sup>2</sup>	
				EnviroPrint Bleach-Fix 70 AC	33 ± 3	70 ml/m <sup>2</sup>	
				EnviroPrint Bleach-Fix 55 AC	33 ± 3	55 ml/m <sup>2</sup>	
				EnviroPrint Bleach-Fix 35 AC	33 ± 3	35 ml/m <sup>2</sup>	
	AP94 BX-NR.		55-110ml/m <sup>2</sup>	EnviroPrint Bleach-Fix 35 RTU AC	33 ± 3	35 ml/m <sup>2</sup>	
			EnviroPrint Bleach-Fix VR AC	33 ± 3	55-108ml/m <sup>2</sup>		

(\*) (reprate 215-645ml/m<sup>2</sup> dep. on TTO 0,3~0,1)

(\*\*) (reprate 215-500ml/m<sup>2</sup>)